

OPzV Solar Power

Eternity Technologies valve regulated lead-acid batteries for the solar power and renewable energy market. With an innovative Gel-Technology design Eternity Technologies OPzV batteries have a reliable maintenance-free and leakage-free construction.

N Part of our Network Power range

Features

High energy density and cyclic performance

Robust tubular positive electrode design, compliant with DIN 40742

>1500 cycles at 80% D.O.D at 20°C (68°F)

Low self discharge rate allows for up to 2 years shelf life

Operating temperature -20°C to +55°C

EUROBAT design life: Long Life > 12 years

Fully recyclable with low CO₂ footprint



Applications

Solar/ Wind Power Stations

Traffic Systems

Hydro Power Generation

Off Grid Solutions

Telecommunications/ Mobile Phone Stations

Power Distribution Companies

Cell specification

Cell Type	Plate (Ah)	Length (mm)	Width (mm)	Height over lid (mm)	Height over pillar (mm)	Typical max weight (kg)	Internal resistance (mOhm)	Short circuit current (A)	Capacity (Ah) C120 - 1.85V Cell at 20°C
4 OPzV-ET 280SOLAR	50	105	208	367	392	18.4	0.95	1650	274
5 OPzV-ET 350SOLAR	50	126	208	367	392	22.2	0.78	2100	345
6 OPzV-ET 400SOLAR	50	147	208	367	392	26.2	0.63	2550	405
5 OPzV-ET 500SOLAR	70	126	208	483.5	509	30.7	0.63	2800	500
6 OPzV-ET 600SOLAR	70	147	208	483.5	509	36.2	0.54	3400	599
7 OPzV-ET 700SOLAR	70	168	208	483.5	509	41.7	0.46	4050	695
6 OPzV-ET 900SOLAR	100	147	208	656	681	50.0	0.51	4350	890
8 OPzV-ET 1200SOLAR	100	212	193	657	682	66.3	0.39	4550	1178
10 OPzV-ET 1500SOLAR	100	212	235	659	684	81.7	0.33	6050	1484
12 OPzV-ET 1800SOLAR	100	212	277	658	683	97.0	0.28	7600	1783
12 OPzV-ET 2000SOLAR	125	212	277	809	834	111.9	0.25	8500	1940
16 OPzV-ET 2600SOLAR	125	215	400	784	809	155.6	0.21	10500	2595
20 OPzV-ET 3300SOLAR	125	214	489	782	807	190.1	0.16	13000	3274
22 OPzV-ET 3600SOLAR	125	214	578	784	809	216.14	0.13	14600	3601
24 OPzV-ET 3950SOLAR	125	214	578	784	809	226.2	0.11	16000	3928
26 OPzV-ET 4250SOLAR	125	214	578	784	809	236.0	0.11	17300	4255

Capacities C10 - C240



Cell Type U _e (100%) / VPC Ref Temp	C10 1.80 20°C	C24 1.80 20°C	C48 1.80 20°C	C72 1.80 20°C	C100 1.85 20°C	C120 1.85 20°C	C240 1.85 20°C
4 OPzV-ET 280SOLAR	214	244	255	270	266	274	282
5 OPzV-ET 350SOLAR	270	308	321	340	336	345	355
6 OPzV-ET 400SOLAR	316	360	376	398	394	405	417
5 OPzV-ET 500SOLAR	391	450	454	485	487	500	515
6 OPzV-ET 600SOLAR	468	538	543	580	583	599	617
7 OPzV-ET 700SOLAR	543	624	630	673	676	695	716
6 OPzV-ET 900SOLAR	696	745	800	870	866	890	917
8 OPzV-ET 1200SOLAR	921	985	1059	1151	1147	1178	1213
10 OPzV-ET 1500SOLAR	1159	1240	1333	1449	1444	1484	1529
12 OPzV-ET 1800SOLAR	1393	1491	1602	1741	1735	1783	1836
12 OPzV-ET 2000SOLAR	1516	1713	1895	1986	1904	1940	1998
16 OPzV-ET 2600SOLAR	2027	2270	2453	2574	2529	2595	2673
20 OPzV-ET 3300SOLAR	2558	2865	3095	3249	3192	3274	3372
22 OPzV-ET 3600SOLAR	2813	3151	3404	3573	3511	3601	3709
24 OPzV-ET 3950SOLAR	3069	3437	3713	3898	3830	3928	4046
26 OPzV-ET 4250SOLAR	3325	3791	4023	4223	4149	4255	4383

Horizontal installation possible up to 12 OPzV-ET 1800SOLAR VO option available


*For horizontal storage of cells larger than 12 OPzV-ET 1800SOLAR please contact Eternity Technologies

H1: Height over lid
H2: Height over pillar
M10 threaded terminal
Torque: 23Nm


Not to scale




**4 OPzV-ET 280SOLAR to
6 OPzV-ET 900SOLAR**



**8 OPzV-ET 1200SOLAR to
12 OPzV-ET 2000SOLAR**




16 OPzV-ET 2600SOLAR



**20 OPzV-ET 3300SOLAR to
26 OPzV-ET 4250SOLAR**

Cycles vs DOD of OPzV Solar Power



OPzV Solar Power

Positive plate

High energy density tubular design with lead calcium alloy ensures low self-discharge rates and low float currents

Negative plate

Industry leading negative plate design

Separator

High-porosity and corrosion-resistant ensures maximum capacity for the lifetime of the cell

Gauntlet

Non-woven, high-capacity polyester gauntlet



Terminal

Maintains an airtight seal even when the plates expand and grow throughout the lifetime of the cell

Electrolyte

Silica-based gel electrolyte that is maintenance free

Pressure release valve

Opens at high pressure to release hydrogen gas created during operation

Container and lid

Manufactured from Acrylonitrile-Butadiene-Styrene (ABS) which is durable and heat resistant

POWER FOR TOMORROW TODAY

The Eternity Technologies range is built using only the highest quality and most efficient production processes at our state-of-the-art manufacturing centre in the UAE.

It is this innovation, modern design criteria and industry-leading machinery that allows Eternity Technologies to not only meet the needs of the global industrial market with increased reliability but define it for the future.



Service



Accessories



Bloc Batteries



Chargers



Network Power



Motive Power



Eternity Technologies FZ-LLC

Al Jazeera / Al Hamra, PO Box 35102,
Ras Al Khaimah, UAE

Sales & service

info@eternitytechnologies.com

www.eternitytechnologies.com