

CLECGOO AUTOMATIC CUTTING SOLUTION

SCAN ME



Cod. 0122



ICUT C600 is the $\mathsf{OROX}^{\scriptscriptstyle(\!R\!)}$ solution designed and developed to cut medium/high productions, in the apparel, furniture, underwear and technical fabrics markets.

The innovative technologies and quality materials build in the ICUT system, grant an high quality and high performance in the cutting production, reducing manpower costs, waste of raw materials, and eliminate the human mistakes in the cutting room.

The several patents in our cutting solutions, combined with cutting-edge hardware-software tools, allow our customers to get competitive advantages and benefits in their production.

The software **ALLCUT X22** with its algorithms, ensures top performances in the cutting production, combining features such as «continuous cutting» system, «zero gap» between the pieces, cut files optimization and advanced management of cutting strategies in the single pieces or in the whole marker.

ICUT technology can be integrated and interfaced with the other tools in the cutting room, in order to create a single data management platform and achieve the goals to speed up and remove the mistakes in the production process.





TECHNICAL FEATURES ICUT C600


Effective cutting height Effective cutting width Effective cutting lenght Discharge conveyor lenght Max power required **Electric requirements Compressed air** Axis speed Accelleration

from single lay up to 6cm compressed 180 | 210 | 225 | 240 | 345cm 175 cm or 210 cm standard 200 cm 19kw single turbine/38kw double Average power consumption 8-9 kw single turbine/14-16 double triphase + neutral 400v50Hz +/-10% 150 L/min 6 Bar 120 meters/min 0.86

Working temperature from -5° C to $+40^{\circ}$ C **Humidity** from 30% to 80% **Noisiness** <75dbA about 2.700 Kg **Machine weight** max 6000 RPM **RPM Knife dimension** 2,5x8mm ISO files File interface Windows 10 **Operating system Processor** intel i5 **Available colors** grey/Red







① Discharge conveyor 150

4,40 m

② Discharge conveyor 200

4.80 m

4.40 m

4,40 m

4.80 m

DIMENSIONS ICUT C600	DIMENSIONS	180x175	180x210	210x175	210x210	225x175	225x210	240x175
	Cutting width	1,80 m	1,80 m	2,10m	2,10m	2,25 m	2,25 m	2,40 m
	Cutting lenght	1,75m	2,10m	1,75m	2,10m	1,75m	2,10 m	1,75 m
	Overall width A	2,80 m	2,80 m	3,00 m	3,00 m	3,15 m	3,15m	3,30 m
	Overall leght B ①	3,90 m	4,40 m	3,90 m	4,40 m	3,90 m	4,40 m	3,90 m

4,40 m

STANDARD TOOLS



Overall leght B ②


«RIVER SYSTEM» - NO STOP CUTTING SYSTEM

4.80 m





DYNAMIC VACUUM MANAGEMENT





TOUCH SCREEN OPERATOR IN THE BEAM





ROBOTIC BEAM PATENTED SYSTEM






DRILL





«TMOV» - MOTORIZED TRANSFER SYSTEM







Oo



«TOUCH» - SECOND TOUCH-SCREEN ON THE BEAM



«EAGLE» - PHOTOGRAPHIC SYSTEM «BARC» - BAR CODE READER



«EDIT CUT» - SOFTWARE TO EDIT AND MANAGE ISO FILES



«FLESE» - INTELLIGENT KNIFE SYSTEM



SECOND VACUUM TURBINE



«SC» - SILICON PLATE



6000 RPM - TOOL

APPLICATIONS





NORTH AMERICA USA

SOUTH AMERICA

Argentina Brazil **El Salvador** Ecuador Colombia Nicaragua Venezuela Uruguay

Poland Romania Bulgaria Moldova Macedonia Russia Lithuania Latvia Belarus Bosnia Herzegovina Serbia Greece **Portugal**

Spain

EUROPE Italy

Turkey Syria Iran **AFRICA** Morocco Tunisia Egypt Uganda

315



www.orox.it info@orox.it









OROX Group Via E.Fermi 6/8 24050 Zanica (BG) Italy

customer care assistenza@orox.it $Ph + 39\ 035.4942582$