



Community Design No: 000235429
 UK Registered Design No: 2098802

Features / Benefits

- Turns your cold water pressurewasher into a hot water pressurewasher
- Works with any Brendon Powerwasher
- Heats water upto 140°C
- 18 Litre Fuel Tank
- Weld free long lasting boiler

Inlet union:	3/8" male
Outlet union:	M22 x 1.5 male
Electric supply:	1~230V-50Hz
Operating pressure:	up to 200 BAR (2900 PSI)
Flow:	6 - 12 LPM
Outgoing water temperature:	30 - 140°C
Fuel tank:	18 litres
Electric cable length:	5.5m
Weight:	92kg

Heats cold water to 140°. Cover and Trolley made of painted sheet metal, two fixed wheels + one caster. New high performance, long-lasting boiler made entirely of stainless steel without any welding. Double turn coil made of steel tube, treated with high temperature paints (30 m). Single phase burner motor directly connected to fan and diesel fuel pump. Control panel with on-off switch and thermostat. Minimum water supply pressure 4 BAR (60 PSI). Safety devices: check valve, safety valve and flowmeter to check lack of water.

Specification may differ per country. Brendon reserves the right to alter the specification without notice.



Sandblasting



Drain Jetting



Mobile Reel



Gulper Kit

Tel: +44 1984 624500 Fax: +44 1984 624501 Email: sales@powerwashers.co.uk