

PROYECTOR ACÚSTICO DE ALUMINIO

EN 60849

SP-12AV **12 W** **102 dB** **bidireccional**

Proyector acústico bidireccional, con recinto cilíndrico de aluminio extrusionado, antivándalo, y grado de protección IP55. Certificación EN-60849



IP55



Potencia RMS	12 W
Selección de potencia (W)	12, 6, 3 y 1,5 W
Respuesta en frecuencia	150 ~ 20.000 Hz
SPL 1 m 1 kHz	91 dB (1 W) / 102 dB (12 W)
Ángulo de dispersión	145° (1 kHz) / 55° (4 kHz)
Protección	IP55 (IEC-529)
Dimensiones (mm)	186 (largo), 146 (boca)
Peso	3,2 kg
Acabados	aluminio extrusionado
Normativa	EN 60849



SP12AV_ES

C/ Barcelona 101
17003 Girona (Spain)
(+34) 972 203 300

OPTIMUS
SOUND & COMMUNICATION

ALUMINIUM ACOUSTIC PROJECTOR

EN 60849

SP-12AV **12 W** **102 dB** **bidirectional**

A bidirectional acoustic projector with extruded aluminium enclosure, vandal resistant and IP55 protection. EN -60849 certification



IP55



RMS power	12 W
Power selection (W)	12, 6, 3 and 1.5 W
Frequency response	150 ~ 20,000 Hz
SPL 1 m 1 kHz	91 dB (1 W)/102 dB (12 W)
Dispersal angle	145° (1 kHz) / 55° (4 kHz)
Protection	IP55 (IEC-529)
Dimensions (mm)	186 (long), 146 (mouth)
Weight	3.2 Kg
Finishing	extruded aluminium
Regulations	EN 60849



SP12AV_EN

C/ Barcelona 101
17003 Girona (Spain)
(+34) 972 203 300

OPTIMUS
SOUND & COMMUNICATION