

AMPLIFICADORES: 30, 60 & 120 W

AM-30 30 W

AM-60 60 W

AM-120 120 W

Amplificadores con 2 entradas de micrófono, una de ellas con prioridad, y una entrada AUX/CD. La prioridad puede activarse desde el micrófono (conector DIN 5P) o desde un pulsador (regleta). Desde el panel frontal se controlan los niveles de las dos entradas de micrófono y de la fuente de música (AUX/CD), así como el volumen de salida general y la ecualización de la señal, de tres bandas (150 Hz, 1 kHz y 6 kHz).

AM-30 / AM-60



AM-120



	AM-30	AM-60	AM-120
Potencia (RMS)	30 W	60 W	120 W
Salidas altavoces	100 y 70 V o 4, 8 y 16 ohm	100 y 70 V o 4, 8 y 16 ohm	100 y 70 V o 4, 8 y 16 ohm
Entrada MIC1 (DIN)	1 mV, 600 ohm, simétrico	1 mV, 600 ohm, simétrico	1 mV, 600 ohm, simétrico
Entrada MIC2 (jack mono 1/4")	1,5 mV, 600 ohm, asimétrica	1,5 mV, 600 ohm, asimétrica	1,5 mV, 600 ohm, asimétrica
Entrada AUX	200 mV, 50 kohm	200 mV, 50 kohm	300 mV, 50 kohm
Entrada CD	1 v, 50 kohm	1 v, 50 kohm	1 v, 50 kohm
Relación señal-ruido	MIC: >60 dB; AUX/CD: >70 dB	MIC: >60 dB; AUX/CD: >70 dB	MIC: >60 dB; AUX/CD: >70 dB
Función de prioridad	MIC 1 sobre resto de entradas	MIC 1 sobre resto de entradas	MIC 1 sobre resto de entradas
Respuesta en frecuencia	100 ~ 20.000 Hz	100 ~ 20.000 Hz	100 ~ 20.000 Hz
Ecualización	150 Hz, 1 kHz y 6 kHz	150 Hz, 1 kHz y 6 kHz	150 Hz, 1 kHz y 6 kHz
Alimentación	230 V CA, 50/60 Hz	230 V CA, 50/60 Hz	230 V CA, 50/60 Hz
Dimensiones (mm)	270 x 90 x 260	270 x 90 x 260	430 x 90 x 270
Peso	4,25 kg	5,0 kg	10,5 kg



AMPLIFIERS: 30, 60 & 120 W

- AM-30** 30 W
- AM-60** 60 W
- AM-120** 120 W

Amplifiers with 2 microphone inputs, one priority, and one AUX/CD input. The priority can be activated from the microphone (DIN 5P connector) or from a button (strip). From the front panel the levels of the two microphone inputs and the music source (AUX/CD) are controlled, as well as the general output volume and the three-band signal equalisation (150 Hz, 1 kHz and 6 kHz).

AM-30 / AM-60



AM-120



	AM-30	AM-60	AM-120
Power (RMS)	30 W	60 W	120 W
Loudspeaker outputs	100 and 70 V or 4, 8 and 16 Ohm.	100 and 70 V or 4, 8 and 16 Ohm.	100 and 70 V or 4, 8 and 16 Ohm.
MIC1 input (DIN)	1 mV, 600 Ohm, symmetric	1 mV, 600 Ohm, symmetric	1 mV, 600 Ohm, symmetric
MIC2 input (jack mono 1/4")	1.5 mV, 600 Ohm, asymmetric	1.5 mV, 600 Ohm, asymmetric	1.5 mV, 600 Ohm, asymmetric
AUX input	200 mV, 50 kohm	200 mV, 50 kohm	300 mV, 50 kohm
CD input	1 v, 50 kohm	1 v, 50 kohm	1 v, 50 kohm
Signal-to-noise ratio	MIC: >60 dB; AUX/CD: > 70 dB	MIC: >60 dB; AUX/CD: > 70 dB	MIC: >60 dB; AUX/CD: > 70 dB
Priority function	MIC 1 on remaining inputs	MIC 1 on remaining inputs	MIC 1 on remaining inputs
Frequency response	100 ~ 20,000 Hz	100 ~ 20,000 Hz	100 ~ 20,000 Hz
Equalising	150 Hz, 1 kHz and 6 kHz	150 Hz, 1 kHz and 6 kHz	150 Hz, 1 kHz and 6 kHz
Power supply	230 Vac, 50/60 Hz	230 Vac, 50/60 Hz	230 Vac, 50/60 Hz
Dimensions (mm)	270 x 90 x 260	270 x 90 x 260	430 x 90 x 270
Weight	4.25 kg	5.0 kg	10.5 kg

