

# The universal Label Dispenser HS 150 with Label Counter

Edition 1



## Label Dispenser HS 150



All current types of adhesive labels can be simply and quickly dispensed by the HS 150 Label Dispenser. Each time a label is removed the next one is automatically brought into position.

The built-in Counter indicates the continually updated total number of labels already dispensed.

An adjustable micro-switch is set to the current label size. In the case of longer labels, first the forward part of the label is made ready to be dispensed. As this part is unpeeled, the micro-switch feeler is released and the

label backing-strip fed further forwards, allowing the remaining part of the label to be removed.

The shape of the labels to be dispensed is unimportant. Both individual and continuous form can be dispensed. In the case of round or oval labels, the micro-switch feeler is moved to the side and positioned at the front edge of the label.

As a result of the powerful motor, label rolls with labels mounted inside or outside, of up to 240 mm. diameter and 150 mm. width can be processed.

### Technical Data

Label width	12 – 150 mm
Label length	min. 15 mm, max. 300
Roll diameter	max. 240 mm
Label rewinding	Inside or Outside
Core diameter	min. 40 mm
Diameter for backing paper	max. 100 mm
Feed supply rate	40 – 100 mm/sec
Justification label length	Microswitch
Quantity display	4 digits, increasing, with reset key
Switch	Power on/off

Electrical	220/230 Volt +6/-10%, 50 Hz 110 Volt +/-10%, 60 Hz
Connection	Power plug
Operating temperature	10 – 35°C with 30 – 85% humidity
Storing- and transport temperature	-20 – 50°C with 10 – 85% humidity
Noise	< 60 dB (A)
Licenses	DIN VDE 0805, IP 20, conforms UL-Norm
Dimensions	Height 188 mm Width 250 mm Depth 240 mm
Weight	4,4 kg



**SOLGE**<sup>®</sup>

SOLUCIONES GLOBALES DE ETIQUETADO

C/Muntaner, 263 bajo int.  
08021 Barcelona  
Tel 93 241 22 21 Fax 93 414 36 18  
www.solge.es ventas@solge.es