



## CARACTERÍSTICAS LM

Tipo LM	Par Nom. Nm	Max. rpm	Agujero			Min. DBSE "S"	Std. DBSE "S"	C	ØA	ØB	* M	Peso kg. Aprox.		M.I. (WR <sup>2</sup> ) in kgm <sup>2</sup> Aprox.		Tors. Stiff. MNm/rad Aprox.
			Min.	Max								Min. Std. "S"	Per Mtr Extra "S"	Min. Std. "S"	Per Mtr Extra "S"	
				Tipo I	Tipo II											
5	33	7500	8	20	22	41	100	25	55	30	65	0.9	2	0.0003	0.0003	0.016
10	64	7500	10	22	25	55	140	30	63	35	75	1.3	2.3	0.0007	0.0004	0.031
35	159	7000	12	30	38	57	100	40	82	45	85	2.47	3.2	0.0021	0.0011	0.025
95	516	6000	17	40	50	82	140	45	102	57	95	4.6	3.2	0.006	0.0011	0.04
170	859	5200	17	52	70	89	180	55	128	77	110	8.1	7	0.018	0.0047	0.099
220	1337	4800	22	65	80	108	140	60	146	94	120	12.1	8.4	0.036	0.0088	0.176
400	2387	4400	27	80	100	114	180	70	176	115	140	20	13.1	0.09	0.021	0.305
520	3342	4200	32	90	115	126	180	90	197	132	175	30.5	21.7	0.17	0.056	0.432
1000	5061	4000	42	105	130	143	250	95	225	147	185	43.4	21.7	0.32	0.056	0.6
1300	7162	3800	47	115	140	168	180	105	250	162	195	61.6	27.1	0.55	0.067	0.8
2000	10027	3700	52	120	155	180	250	115	275	178	215	82	42.8	0.88	0.167	1.5
2500	13369	3600	62	135	165	180	300	130	300	190	235	107.1	42.8	1.38	0.167	1.4

## CARACTERÍSTICAS LMK

Tipo LMK	Par Nominal Nm	Max rpm	Agujero			DBSE G	C	ØA	ØB	* M	Peso kg. Aprox.	M.I. (WR <sup>2</sup> ) in kgm <sup>2</sup> Aprox.	Torsional Stiffness MNm/rad Aprox.
			Min.	Max									
				Tipo I	Tipo II								
5	33	7500	8	20	22	5.2	25	55	30	65	0.55	0.00020	0.0360
10	64	7500	10	24	25	6.5	30	63	35	75	0.87	0.00030	0.0430
35	159	7000	12	30	38	6.5	40	82	45	85	1.8	0.0008	0.062
95	516	6000	17	40	50	8	45	102	57	95	3.2	0.0026	0.118
170	859	5200	17	52	70	9.5	55	128	77	110	5.83	0.0087	0.260
220	1337	4800	22	65	80	12	60	146	94	120	8.4	0.017	0.492
400	2387	4400	27	80	100	13	70	176	115	140	14.1	0.045	1.228
520	3342	4200	32	90	115	14.4	90	197	132	175	22.1	0.089	1.926
1000	5061	4000	42	105	130	16.2	95	225	147	185	30.7	0.16	3.613
1300	7162	3800	47	115	140	19.5	105	250	162	195	42.8	0.27	CONSULTAR
2000	10027	3700	52	120	155	21.5	115	275	178	215	57.6	0.44	
2500	13369	3600	62	135	165	23.5	130	300	190	235	76.2	0.67	