

# 2830

## Strapping machine Horizontal semiautomatic for pallets

Easy to use. The machine can be placed beside the stacked pallet, avoiding the need to move the load.

- Own manufacturing and technology using highest quality components.
- ·Aluminium head set and tension roller treated ensures long life of the machine.
- ·Tension electronically adjustable through a magnetic clutch to get the strongest tension without any physical effort.
- ·Dual power supply system: To network and with batteries.
- ·Strapping height manually adjustable without effort. Allows strap from 17 cm. from the floor up to 2 m.
- It helps putting edge protectors while first strapping and easy transportation to the place of operation.
- ·Brake lever to prevent unwanted movements.
- ·Bobbin holder located on the base to facilitate bobbin change
- ·Market leader in semiautomatic strapping in fruit and vegetable sector since 1994.



REISO1400 strapping head long durability

and excellent performance.

Forget failures!



Compatible with 400 mm coils to reduce the number of stops.

> Brake lever to prevent unwanted movements.





Reisopack s.l.

## **CHARACTERISTICS**

**VOLTAGE**: 220 V / 240 V · 50 / 60 Hz. Single phase

ELECT. CONSUMPTION: 1 Kw. APROX. PRODUCT.: 20-30 pallets / hour.

**BATTERY DURATION:** 600 straps.

PACKAGING DIMENSIONS: 2 packages (440 Kg.).

1150 X 1070 X 1070 mm. / 2450 X 760 X 670 mm.

### TECHNICAL SPECIFICATIONS

STRAP WIDTH: 6-8-12-16 mm. (Factory set).

STRAP THICKNESS: 0,50-0,85 mm.

**HEATING SYSTEM**: Electrical heating.

Heating temperature and cooling time adjustable.

OPTIONS: Corners deposit.

Inner diameter of the bobbin holder of 200mm or 400mm.

2830

zontal semiautomatic for pallets

Polígono Industrial "Z' C/ De la Premsa, 3 08150 Parets del Vallès (Spain)

Tel. 902 153 448 · Fax 935 624 186 http://www.reisopack.com E-mail: reiso@reisopack.com