



Touch Probe TC52



For small machining centres compact touch probe with multidirectional measuring mechanism

- Detection of workpiece position
- Correction of workpiece orientation
- Thermal compensation of the machine tool
- Contour measurement


Your benefit:

- Measuring speed up to 2 m/min
- Precise, non-lobing touch characteristics
- No-wear, optoelectronic measuring mechanism
- Use of two measuring systems with one IR receiver
- Extended battery life
- Precise measurement even with coolant
- Proven and robust design



DUO-Mode

Sequential use of two measuring systems with one infrared receiver.




Ø13

0






Fast workpiece measurement



Non-lobing touch characteristics



Modern and precise measuring mechanism with optoelectronic signal generation

Technical data

Protection class	IP68
Approach directions	±X, ±Y, -Z
Measuring force in XY Z	2,3 N / 0,65 N (LF)* 5,7 N / 1,6 N (LF)*
Max. deflection XY Z	± 11° 6 mm
Max. acceleration	50 m/s ²
Repeatability	0,3 μm 2σ
Max. probing speed	2 m/min
Mass	250 g
Signal transmission Range	Infrared ± 60 ° in Z, 360 ° in X/Y
Battery	Saft Lithium LS14250 (½AA, 3,6V) 1200 mAh
Tool holder	BTH 25 (HSK, SK, BT, VDI,)
Storage/Operating temperature * Stylus L= 30 mm	-20 °C +70 °C +5 °C +50 °C



Blum worldwide Service & Support

More than 40 subsidiaries and service offices.

www.blum-novotest.com

Blum-Novotest Ltd.

33 Townfields Lichfield, Staffordshire WS13 8AA, United Kingdom

Phone: +44 1543 257111 Fax: +44 1543 251746 E-Mail: info@blum-novotest.co.uk Blum LMT, Inc. 4144 Olympic Boulevard

Erlanger, KY 41018 USA

Phone: +1 (859) 344 6789 Fax: +1 (859) 344 6799 E-Mail: solutions@blumlmt.com