



Touch Probe TC53-10



## Modular and compact - touch probe for custom measuring tasks with revolutionary shark360 measuring mechanism

- · Special measuring tasks with a wide range of accessories
- Pulling measurements
- Thermal compensation of the machine tool


## Your benefit:

- · Customized adaptions are easily developed
- Superior precision due to patented shark360 measuring mechanism
- No-wear, optoelectronic measuring mechanism
- Use of two measuring systems with one IR receiver
- Extended battery life

**DUO-Mode** 


- Precise measurement even with coolant
- Compact and robust design

Sequential use of two measuring systems with one infrared receiver.





Workpiece measurement on turning machine



Fast workpiece measurement in rotary transfer machine



**Technical data** 

Protection class	IP68
Approach direction	±X, ±Y, ±Z
Measuring force in XY   Z	1,3 N   5,9 N (LF 0,4 N*   2,0 N*)
Max. deflection XY   Z	± 15°   5 mm
Max. acceleration	50 m/s <sup>2**</sup>
Repeatability	0,4 μm 2σ
Max. probing speed	2 m/min
Mass	305 g (Without accessories, e.g. extension, angle)
Signal transmission   Range	Infrared   ± 60° in Z, 360° in XY
Battery (2 pieces)	Saft Lithium LS14250, (½ AA, 3,6V) 1200 mAh
Tool holder	BTH 25 (HSK, SK, BT, VDI,)
Storage/Operating temperature	-20 °C +70 °C   +5 °C +50 °C



\*\* With accessories (e.g. extension, angle): max. acceleration  $10\ m/s^2$ 



Various accessories available



shark360 measuring mechanism



Blum worldwide Service & Support

More than 40 subsidiaries and service offices.

www.blum-novotest.com

Blum-Novotest Ltd.

33 Townfields Lichfield, Staffordshire WS13 8AA, United Kingdom

Phone: +44 1543 257111 E-Mail: info@blum-novotest.co.uk Blum LMT, Inc. 4144 Olympic Boulevard Erlanger, KY 41018 USA

Phone: +1 (859) 344 6789 Fax: +1 (859) 344 6799 E-Mail: solutions@blumlmt.com