



Touch Probe TC53-30




Touch probe for special applications – modular system with reinforced design and revolutionary shark360 measuring mechanism

- · Special measuring tasks with custom extensions
- Pulling measurements
- Thermal compensation of the machine tool

Your benefit:

- Customized adaptions are easily developed
- Superior precision due to patented shark360 measuring mechanism
- No-wear optoelectronic measuring mechanism
- Use of two measuring systems with one IR receiver
- · Extended battery life
- · Precise measurement even with coolant
- · Compact and robust design





Workpiece measurement in turn-mill machine

Mass production of gearbox housings

DUO-Mode

Sequential use of two measuring systems with one infrared receiver.



Technical data

Protection class	IP68
Approach direction	±X, ±Y, ±Z
Measuring force in XY Z	1,3 N 5,9 N (LF: 0,4 N* 2,0 N*)
Max. deflection XY Z	± 15° 5 mm
Max. acceleration	50 m/s**
Repeatability	0,4 μm 2σ
Max. probing speed	2 m/min
Mass	790 g (Without accessories, e.g. extension, angle)
Signal transmission Range	Infrared \mid ± 60° in Z, 360° in XY
Battery (2 pieces)	Saft Lithium LS 14500 (AA, 3,6V) 2600 mAh
Tool holder	BTH 50 (HSK, SK, BT, VDI,)
Storage/Operating temperature	-20 °C70 °C +5 °C +50 °C



Various accessories available



shark360 measuring mechanism



Blum worldwide
Service & Support

More than 40 subsidiaries and service offices.

www.blum-novotest.com

Blum-Novotest Ltd.

33 Townfields Lichfield, Staffordshire WS13 8AA, United Kingdom

Phone: +44 1543 257111 Fax: +44 1543 251746 E-Mail: info@blum-novotest.co.uk **Blum LMT, Inc.** 4144 Olympic Boulevard Erlanger, KY 41018

USA

Phone: +1 (859) 344 6789 Fax: +1 (859) 344 6799 E-Mail: solutions@blumlmt.com