


TCD 4.1/6.1

STAGE
ready **V**

For mobile machinery
80 - 180 kW | 108 - 241 hp at 1800 - 2300 min⁻¹ | rpm
EU Stage IV / US EPA Tier 4

- Water-cooled 4 or 6-cylinder inline engines with turbocharging, charge air cooling and cooled external exhaust gas recirculation.
- Engine and exhaust aftertreatment (EAT) are optimised for highest total system efficiency and thus ensure minimised fuel and total operating costs.
- Consistent installation and connection dimensions of the engine facilitate the changeover of existing installations to the next stage of the emission laws. The size and design of the engines will remain identical in the change to Stage V due to a protected technology. No changes to the customer's device. A variant without EAT is available as an option for less regulated markets.



- The powerful DEUTZ Common Rail (DCR®) injection system and the electronic engine control (EMR 4) with intelligent link to the drive management ensure optimum engine performance at low fuel consumption.
- Best cold starting performance even under extreme conditions.
- Long oil change intervals and easy changing of the engine fluids reduce the running costs and increase the availability of the machinery.
- The extremely compact engine design and customer friendly accessories reduce the installation costs and increase the number of applications.
- 100% power take-off at flywheel and front end, and additionally up to three PTO drives with a total torque of up to 315 Nm.
- The engines meet the requirements of the EU Stage IV and US EPA Tier 4 with DVERT® selective catalytic reduction (SCR) and particulate filter (DPF). Through the use of the DPF they already comply with the EU Stage V emissions standard expected from 2019.*

Technical data

Engine type		TCD 4.1 L4	TCD 6.1 L6
No. of cylinders		4	6
Bore/stroke	mm in	101/126 4.0/5.0	101/126 4.0/5.0
Displacement	l cu in	4.1 250	6.1 370
Max. nominal speed	min ⁻¹ rpm	2300	2300

Power output		TCD 4.1 L4	TCD 6.1 L6
Power output as per ISO 14396 ¹⁾	kW hp	115 154	180 241
at speed	min ⁻¹ rpm	2300	2300
Max. torque	Nm lb/ft	610 450	1000 738
at speed	min ⁻¹ rpm	1600	1450
Minimum idling speed	min ⁻¹ rpm	600	600
Specific fuel consumption ²⁾	g/kWh lb/hph	208 0.34	200 0.33
Weight as per DIN 70020 Part 7A ³⁾	kg lb	400 882	620 1367

* Based on the proposal by the EU Commission COM (2014) 581 final from 25.09.2014.

1) Power data without deduction of fan power.

2) Best point consumption refers to diesel with a density of 0.835 kg/dm³ at 15°C.

3) Without starter/alternator, cooler and fluids but with flywheel and flywheel housing.


The data on this data sheet are for information purposes only and are not binding values. The data in the quotation is definitive.

The engine company.




Torque curve




TCD 4.1 L4 - 115 kW|154 hp



TCD 6.1 L6 - 180 kW|241 hp



Dimensions



					DPF		SCR		DVERT® EAT	
					D	L	D	L	DPF	SCR
TCD 4.1 L4 T4	mm in	851 33.5	617 24.3	884 34.8	246 9.7	698 27.5	246 9.7	659 25.9	■	■
TCD 6.1 L6 T4	mm in	1082 42.6	678 26.7	946 37.2	272 10.7	782 30.8	272 10.7	689 27.1	■	■

■ Standard

Note: The engine dimensions and weights vary depending on the scope of delivery.

Order no. 0031 2272 / 03 / 2015 / MC-M

For more information please contact the DEUTZ AG Köln or the responsible sales partner.



DEUTZ AG • Ottostraße 1 • 51149 Köln • Deutschland • Telefon +49 (0) 221 822-0 • Telefax +49 (0) 221 822-3525 • www.deutz.com • E-Mail: info@deutz.com