

D-53 PLT PALLET STRAPPING MACHINE



Innovative semi automatic palletizer.
Handy and economical way
to secure your pallets!



▪ VERSATILE TENSION CAPABILITY

Manual Tension or Automatic Tension are available by means of a simple selector switch.

<Manual Tension Mode>

The strap tension can be controlled manually via the Operation Bar, allowing edge protection to be secured to the pallet prior to strap completion.

<Auto Tension Mode>

Strap tension is applied automatically at a preselected level.

▪ SIMPLE OPERATION

Operator friendly! Only the use of the Operation Bar (Manual Tension) and the Start Switch are needed for complete strap operation.

▪ 4-WAY PALLET ENTRY

The bayonet height can be adjusted (25mm and 15mm, 1" and 3/5") by a simple lever.

Allows cross strapping through various sized pallet openings.



▪ LOWER SEALING FOR SMALL PALLET

Sealing Point is only 327mm (12 7/8") from the floor.

Small height pallets can now be strapped easily.

SPECIFICATIONS

Width	2210 mm
Height	1012 mm
Depth	756 mm
Machine Weight	approx 100 kg
Arch Height	15,25 mm
Package Size	min. 380 mm / 15" (Height)

Strap Width	6, 9, 12 mm
Strap tension	9-690N (9-70kgf)
Sealing Method	heat seal
Power Supply	100, 110, 120, 200, 220, 230, 240V Single Phase 50/60Hz 0.4kw



COMOSA STRAPP, S/A

C/. Bac, nave 1 y 2 (Políg. Ind. Foinvasa)

Telf. (93) 575 08 44

Fax (93) 564 71 94

08110 MONTCADA I REIXAC

(Barcelona)