## AUTOMATIC STRAPPING MACHINE





# **RQ-8**

## High-Performance Automatic Strapping Machine

#### Amazing Strapping Speed

1.5 seconds per strapping cycle -That's 40 straps per minute!

#### Self-Correcting Technology

Unique self-correcting mechanisms are built into the RQ-8 operation. If the RQ-8 is operated accidentally without a package on the table, the strap will form a small loop which will be automatically ejected from the sealing unit leaving the machine ready for the next cycle.

#### Easy Strap Loading

Newly developed loading system free of complicated devices makes strap threading almost completely automatic -it's just a touch of a lever.

#### 1252 (49-5/16) 914 (36) 338 609 (24) (13-5/16) 650 (25) (24) 609 498 (19) 403 (55-1/4) 794 (31-1/4) 5/8) 10 20 F 6 513 (20-3/16) millimeters / (inches

#### Permanently Lubricated Mechanisms

Strapack's self-lubricating design has an unsurpassed reputation for its durability and maintenance-free operation.

CE

#### Quick Heater

Ready to operate in less than 25 seconds. Designed to insure high seal joint.

#### Self-diagnostic

A programmable microprocessor constantly monitors critical functions. Any irregularity sensed is immediately displayed.

#### Portable

Heavy-duty metal casters allow for the machine to be quickly installed or moved to any Single Phase power supply outlet.

#### Variable Tension

A wide range of tension is available to the operator by use of a single tension dial. Tension capability up to 80kg (equivalent to 150mm stroke).

#### Dependable

Strapack's advanced bandway design assures perfect strap placement and eliminates any twisted straps.

		RQ – 8
Dimensionqqs	Width	1252 mm
	Height	1403 mm
	Depth	609 mm
	Weight	160 kg
Table Height		794 mm
Arch Size		W 650 x H 500 mm
Package Size	Max	W 620 x H 480 mm
	Min	W 80 x H 30 mm
Joint / Strap / Coil		Heat seal / polypropylene/ ID 200 x OD 450 X W 200 mm
Strap Width		Up to 80 kg stroke 150 mm
Speed		1.5 sec. / strap, 40 straps per min.
Power Supply		100, 120, 200, 220, 230, 240V Single Phase 50/60 Hz 0.65 KVA



### COMOSA STRAPP, S/A

C/. Bac, nave 1 y 2 (Políg. Ind. Foinvasa) Telf. (93) 575 08 44 Fax (93) 564 71 94 08110 MONTCADA I REIXAC (Barcelona)

## Standaqrd Specifications