

DuraMON Glass 19" LED RADAR / ECDIS



DuraMON LED monitors are designed for marine and naval mission critical applications.

It values markets demands for:

- Standardisation and easy integration.
- Simplicity in operation.
- Modular & space saving.
- Low weight
- Long up time and less service.
- Long built-state possibility.
- Zero Mercury
- Low Power consumption.

- High quality display 19" 5:4 format
- Compliant with IEC 60945 and IACS E10.
- ECDIS / RADAR options.
- LED Backlight
- Full range backlight dimming
- Keys dimming control options.
- Desk/Roof and wall mounting-brackets available.
- Optional Touch and Buzzer.
- Optional ECDIS calibration

Distribuido por: AN Consult España | Tel.: 91 613 00 31 | Fax: 91 613 65 06 | comercial@anconsult.com

Specifications

DuraMON LED

Display sizes: 19" LCD (TFT)

Display properties:	Size – Active area (Aspect)	Luminance	Contrast	Resolution
	19" - 376 x 301 mm (4/3)	300 Cd/m ²	2000:1	1280 x 1024

View angle: 89° - 89° (L/R/T/B) (typical)

Materials: Front: Sea Water Resistant Aluminium w. black power coating RAL 9005

Rear: Sea Water Resistant Aluminium w. black power coating RAL 9005

Window: Anti Reflection coated front glass

Protection: IP65 front – IP20 rear

DuraMON LED I/O

Video inputs: RGB : Analogue 0.7 Vpp positive at 75Ω,
Separate sync or sync on green
Generally all VESA compatible video modes are supported up to 165MHz (up to UXGA 60Hz and WUXGA 60Hz reduced blanking).
Horizontal sync: 15-100 kHz (automatic)
Vertical sync: 30-85 Hz up to 1280x1024
30-60 Hz up to 1920x1200

DVI: Generally all VESA compatible video modes are supported up to 160MHz (up to UXGA 60Hz and WUXGA 60Hz reduced blanking).
Special modes supported on request.

Option available for S-video and Composite video

Control inputs: 1x RS232 – for remote control
Option available for Touch 1x USB
Option available for integrated Alarm Buzzer

DuraMON LED Power Supply Options

Standard: 90-264Vac. 50-60Hz Input

Optional: 18-36Vdc Input
Dual power, AC/DC (option)

DuraMON LED Environmental Conditions

Operating Temperature: -15 to 55 °C

Storage Temperature: -25 to 70 °C

Relative Humidity: 8 to 90 %

DuraMON LED Approvals

CE Mark: EN61000-6-2 & EN61000-6-4

Marine: IACS E10 Rev. 5 & IEC 60945 Ed. 4

ECDIS: IEC 61174

Radar / Navigation: IEC 62388 and IEC 62288

Type Approvals: DNV Mutual Recognition

For latest marine class approvals – see www.isic-systems.com

DuraMON LED Physical dimensions

Size: 429 (W) x 382 (H) x 85 (D)

Weight: 8 kg.

Bracket: Desk / wall / roof bracket and IP22 rear-cover available (optional extra)

